




## ACCESSORY


BRACKET TYPE

RECESS FRAME TYPE

## DIMENSION



## LIGHT DISTRIBUTION



SPECIFICATION					
POWER	80W. / 100W. / 150W. / 250W.				
MODEL NAME	LHB29				
NAME	LED High Bay				
LIGHT SOURCE	LED Module SMB				
DRIVER	Integrated driver				
LUMEN	12000LM / 15000LM / 22500LM / 30000LM				
LUMEN/WATT	150 lm/W				
BEAM ANGLE	115°				
COLOR TEMPERATURE	3000K / 4000K / 5000K / 6500K				
COLOR RENDERING INDEX (Ra)	80				
INPUT VOLTAGE	100 - 277Vac				
INPUT FREQUENCY	50/60Hz				
POWER FACTOR	0.90				
MATERIAL	Housing material : Corosion resistant no harmful substance or chemicals and power coated Optical cover/lens type : High quality PC lens				
DIMENSION	<table border="1"> <thead> <tr> <th>Ø (mm.)</th> <th>Height (mm.)</th> </tr> </thead> <tbody> <tr> <td>430</td> <td>190</td> </tr> </tbody> </table>	Ø (mm.)	Height (mm.)	430	190
Ø (mm.)	Height (mm.)				
430	190				
WEIGHT	12.3 kg				
IK RATING	IK06				
IP RATING	IP65				
OPARATING TEMPERATURE	-40 to +45 °C				
CERTIFICATE					
DIMMABLE	No (option Dimmable 0-10V)				
LIFE TIME	50,000 hours				
WARRANTY					
OTHER					