




ACCESSORY

DIMENSION



LIGHT DISTRIBUTION

SPECIFICATION																																																																																					
POWER	40W/50W/60W/80W/90W/100W/120W/150W/180W/200W/240W																																																																																				
MODEL NAME	LHB30																																																																																				
NAME	LED High Bay																																																																																				
LIGHT SOURCE	CREE XTE																																																																																				
DRIVER	MEANWELL																																																																																				
LUMEN	4400LM/5500LM/6600LM/8800LM/9900LM/11000W/13200W/16500LM/19800LM/22000LM/26400LM																																																																																				
LUMEN/WATT	110 lm/W																																																																																				
BEAM ANGLE	25°/45°/60°/90°																																																																																				
COLOR TEMPERATURE	3000K / 6500K																																																																																				
COLOR RENDERING INDEX (Ra)	80																																																																																				
INPUT VOLTAGE	220Vac																																																																																				
INPUT FREQUENCY	50/60Hz																																																																																				
POWER FACTOR	0.97																																																																																				
MATERIAL	Housing material : Corosion resistant no harmful substance or chemicals and power coated Optical cover/lens type : High quality PC lens																																																																																				
DIMENSION	<table border="1"> <thead> <tr> <th>Watt</th> <th>W1</th> <th>W2</th> <th>L1</th> <th>L2</th> <th>H</th> <th>Watt</th> <th>W1</th> <th>W2</th> <th>L1</th> <th>L2</th> <th>H</th> </tr> </thead> <tbody> <tr> <td>40</td> <td>400</td> <td>340</td> <td>215</td> <td>150</td> <td>100</td> <td>120</td> <td>400</td> <td>340</td> <td>390</td> <td>330</td> <td>100</td> </tr> <tr> <td>50</td> <td>400</td> <td>340</td> <td>215</td> <td>150</td> <td>100</td> <td>150</td> <td>400</td> <td>340</td> <td>390</td> <td>330</td> <td>100</td> </tr> <tr> <td>60</td> <td>400</td> <td>340</td> <td>300</td> <td>240</td> <td>100</td> <td>180</td> <td>400</td> <td>340</td> <td>480</td> <td>420</td> <td>100</td> </tr> <tr> <td>80</td> <td>400</td> <td>340</td> <td>300</td> <td>240</td> <td>100</td> <td>200</td> <td>400</td> <td>340</td> <td>480</td> <td>420</td> <td>100</td> </tr> <tr> <td>90</td> <td>400</td> <td>340</td> <td>300</td> <td>240</td> <td>100</td> <td>240</td> <td>400</td> <td>340</td> <td>570</td> <td>510</td> <td>100</td> </tr> <tr> <td>100</td> <td>400</td> <td>340</td> <td>300</td> <td>240</td> <td>100</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Watt	W1	W2	L1	L2	H	Watt	W1	W2	L1	L2	H	40	400	340	215	150	100	120	400	340	390	330	100	50	400	340	215	150	100	150	400	340	390	330	100	60	400	340	300	240	100	180	400	340	480	420	100	80	400	340	300	240	100	200	400	340	480	420	100	90	400	340	300	240	100	240	400	340	570	510	100	100	400	340	300	240	100						
Watt	W1	W2	L1	L2	H	Watt	W1	W2	L1	L2	H																																																																										
40	400	340	215	150	100	120	400	340	390	330	100																																																																										
50	400	340	215	150	100	150	400	340	390	330	100																																																																										
60	400	340	300	240	100	180	400	340	480	420	100																																																																										
80	400	340	300	240	100	200	400	340	480	420	100																																																																										
90	400	340	300	240	100	240	400	340	570	510	100																																																																										
100	400	340	300	240	100																																																																																
WEIGHT																																																																																					
IK RATING																																																																																					
IP RATING	IP65																																																																																				
OPARATING TEMPERATURE																																																																																					
CERTIFICATE																																																																																					
DIMMABLE	No																																																																																				
LIFE TIME	50,000 hours																																																																																				
WARRANTY																																																																																					
OTHER																																																																																					